

Scooter Service & Support

Rev Maintenance & Service

- Removing Standing Platform
- Hand Brake Assembly Replacement
- Handlebar Assembly Replacement
- Grips Replacement
- Bell Replacement
- Stem Catch Replacement**
- Secondary Lock Replacement
- Brake Maintenance Instructions
- Cleaning the Charging Port
- Front Fender Replacement
- Kickstand Replacement
- Tire & Tube Replacement
- Motor Assembly Replacement
- Skid Rail Replacement
- Battery Replacement
- Headlight Replacement

Stem Catch Replacement

Difficulty Rating: 1

Estimated Time: less than 5 minutes

Tools you will need:

- 2mm hex key
- Thin pliers or tweezers



1. Remove the screws on both sides of the stem catch using a 2mm hex key.



2. The stem catch can now be removed. It can help to use tweezers, or thin pliers to pull it off.



3. Slide new stem catch onto the stem until it latches into place.



4. Reinstall the screws on both sides with a 2mm Allen wrench.



Was this article helpful?

9 out of 13 found this helpful

Comments

0 comments

Article is closed for comments.

Help

Can't find what you're looking for?

SUBMIT A REQUEST

Company

- Contact Us
- Press
- Careers
- Terms and Conditions
- Privacy Policy
- Safety and Compliance

Explore

- Community
- Reviews
- Videos
- Dealer Locator

Orders

- Shop Boards
- Accessories
- Support

Subscribe to our Newsletter

email address

